




GENERAL TOLERANCE

DIM. RANGE	0.5 ~ 3	> 3 ~ 6	> 6 ~ 30	> 30 ~ 120	> 120 ~ 400	SURFACE FINISH
TOLERANCE	±0.1	±0.1	±0.2	±0.3	±0.5	1.6


CUSTOMER DRAWING

REVISIONS


REV	DESCRIPTION	DATE
A	INITIAL RELEASE	2020-07-13



PRE-ASSEMBLY
WHILE SHIPPING



WIRE GUIDE LOSSE MOUNTED (AT TIME OF SUPPLY)



NOTES:

- THE PRODUCTS ARE RoHS COMPLIANCE.
- MATERIAL SPEC:
HOUSING: PA4TTHREMOPLASTIC,UL94 V-0,BLACK COLOR.
CONTACT:COPPER ALLOY,MATING AREA GOLD PLATING,OTHER AREA TIN PLATING.

UNLESS OTHERWISE SPECIFIED	SPECIFICATIONS	POS	QTY	PART NUMBER	DESCRIPTION	NOTE
LINEAR DIMENSIONS ARE IN: MILLIMETERS TOLERANCES: ANGLES= ±2° DEFAULT LINEAR TOLERANCES SEE TABLE DIM.& TOL. PER ASME Y14.5M-1994; DRM PER MIL-DTL-31000; LEGENDS: △ =FLAG NOTE CALL OUT REFERENCE ONLY	MATERIAL SPEC.	PARTS LIST				
	SEE NOTES 2	APPROVALS				
	PROCESS SPEC.	THIRD ANGLE PROJECTION				
		SCALE: 11.0				
		DATE		上海良速电子有限公司		
		Jul-14-20		Powerlite		
				1.27mm Single Row 4pin Female 90° cable outlet		
		DOCUMENT NO.		PL-FA04101		REV. A