

4







3

2

GENERAL TOLERANCE						
DIM. RANGE	0.5 ~ 3	> 3 ~ 6	> 6 ~ 30	> 30 ~ 120	> 120 ~ 400	SURFACE FINISH
TOLERANCE	±0.1	±0.1	±0.2	±0.3	±0.5	1.6


CUSTOMER DRAWING

REVISIONS			
REV	DESCRIPTION	DATE	



RECOMMENDED PCB-LAYOUT

- NOTES:
- THE PRODUCTS ARE ROHS COMPLIANCE.
 - MATERIAL SPEC: HOUSING: LCP THERMOPLASTIC,UL94 V-0,BLACK COLOR, CONTACT: COPPER ALLOY,MATING AREA GOLD PLATING,OTHER AREA TIN PLATING.
 - COPLANARITY AREA OF TERMINATION ≤0.1mm.

UNLESS OTHERWISE SPECIFIED		SPECIFICATIONS		POS	QTY	PART NUMBER	DESCRIPTION	NOTE
LINEAR DIMENSIONS ARE IN: MILLIMETERS TOLERANCES: ANGLES: ±2° DEFAULT LINEAR TOLERANCES SEE TABLE DIM. & TOL. PER ASME Y14.5M-1994; DRW PER MIL-DTL-31000;		MATERIAL SPEC.		APPROVALS		DATE	上海良速电子有限公司 Powermax 16pin dual vertical male SMT	U
		SEE NOTES 2		PREPARED BY	JUSTIN LI			
				ENGINEER IN CHARGE	TYLER QIU	2020/6/1		
				DESIGN MANAGER	TYLER QIU			
				DESIGN ACTIVITY GROUP				
LEGENDS: =FLAG NOTE CALL OUT REFERENCE ONLY		PROCESS SPEC.		THIRD ANGLE PROJECTION				
		--						
				SCALE:				
		SIZE		DOCUMENT NO.		REF.		
		C		PM-MV16201				