

4






3

2

GENERAL TOLERANCE							
DIM. RANGE	0.5 ~ 3	> 3 ~ 6	> 6 ~ 30	> 30 ~ 120	> 120 ~ 400	SURFACE FINISH	
TOLERANCE	±0.1	±0.1	±0.2	±0.3	±0.5	1.6	


CUSTOMER DRAWING

REVISIONS			
REV	DESCRIPTION	DATE	



RECOMMENDED PCB-LAYOUT

- NOTES:
- THE PRODUCTS ARE ROHS COMPLIANCE.
 - MATERIAL SPEC:
HOUSING: LCP THERMOPLASTIC,UL94 V-0,BLACK COLOR.
CONTACT: COPPER ALLOY,MATING AREA GOLD PLATING,OTHER AREA TIN PLATING.
 - COPLANARITY AREA OF TERMINATION ≤0.1mm.

UNLESS OTHERWISE SPECIFIED		SPECIFICATIONS		POS	QTY	PART NUMBER	DESCRIPTION	NOTE
LINEAR DIMENSIONS ARE IN: MILLIMETERS TOLERANCES: ANGLES: ±2° DEFAULT LINEAR TOLERANCES SEE TABLE DIM. & TOL. PER ASME Y14.5M-1994; DPM PER MIL-DTL-31000;		MATERIAL SPEC.		APPROVALS DATE PREPARED BY JUSTIN LI ENGINEER IN CHARGE TYLER QIU DESIGN MANAGER TYLER QIU DESIGN ACTIVITY GROUP 2020/5/6 THIRD ANGLE PROJECTION 				
		SEE NOTES 2						
		PROCESS SPEC.						
		--						
LEGENDS:  =FLAG NOTE CALL OUT REFERENCE ONLY								
				上海良速电子有限公司 Powermax 22pin dual row RA male SMT connector U				
		SIZE		DOCUMENT NO.		REF.		REV.
		C		PM-MA22201				A
		SCALE:				SHEET 1 OF 1		