

4







3

2

GENERAL TOLERANCE						
DIM. RANGE	0.5 ~ 3	> 3 ~ 6	> 6 ~ 30	> 30 ~ 120	> 120 ~ 400	SURFACE FINISH
TOLERANCE	±0.1	±0.1	±0.2	±0.3	±0.5	1.6

CUSTOMER DRAWING

REVISIONS			
REV	DESCRIPTION	DATE	



RECOMMENDED PCB-LAYOUT

- NOTES:
- THE PRODUCTS ARE ROHS COMPLIANCE.
 - MATERIAL SPEC:
HOUSING: LCP THERMOPLASTIC,UL94 V-0,BLACK COLOR.
CONTACT: COPPER ALLOY,MATING AREA GOLD PLATING,OTHER AREA TIN PLATING.
 - COPLANARITY AREA OF TERMINATION ≤0.1mm.

UNLESS OTHERWISE SPECIFIED		SPECIFICATIONS		POS	QTY	PART NUMBER	DESCRIPTION	NOTE
LINEAR DIMENSIONS ARE IN: MILLIMETERS TOLERANCES: ANGLES: ±2° DEFAULT LINEAR TOLERANCES SEE TABLE DIM. & TOL. PER ASME Y14.5M-1994; DPM PER MIL-DTL-31000;		MATERIAL SPEC.		上海良速电子有限公司 Powermax 16pin dual row RA male SMT connector				
		SEE NOTES 2						
		PROCESS SPEC.						
		--						
		THIRD ANGLE PROJECTION						
LEGENDS:  =FLAG NOTE CALL OUT REFERENCE ONLY		APPROVALS		U				
		PREPARED BY ENGINEER IN CHARGE		JUSTIN LI		DATE		
		DESIGN MANAGER		TYLER QIU		2020/5/6		
		DESIGN ACTIVITY GROUP		TYLER QIU				

A

B

C

D

4

3

2

1